

규격서 (사양설명서)

품명	<p>국문 : RF 계측기 표준 교정도구 영문 : RF Gender and Adaptor</p>
모델명	
Description	<ul style="list-style-type: none"> ● Coaxial Adaptor P-Type(F) to SMA(F) : 20EA <ul style="list-style-type: none"> - DC to 18 GHz - SMA 3.5mm - Insertion Loss : 0.43(Maximum) per mated pair dB - Max. SWR : 1.10 - Repeatability: SMA:0.010~0.020dB / Type N:<0.006 ~0.010dB ● Coaxial Adaptor P-Type(M) to SMA(F) : 20EA <ul style="list-style-type: none"> - DC to 18 GHz - SMA 3.5mm - Insertion Loss : 0.43(Maximum) per mated pair dB - Max. SWR : 1.10 - Repeatability: SMA:0.010~0.020dB / Type N:<0.006 ~0.010dB ● SMA Termination Port (M) : 20EA <ul style="list-style-type: none"> - DC to 18 GHz - SMA 3.5mm - Average Power : 10 watts - Peak Power : 1 kwatts - SWR : 1.20 ~ 1.35 ● Power Attenuator 10 dB : 4EA <ul style="list-style-type: none"> - DC to 18 GHz - Type N (F) to Type N (F) - Average Power : 100 watts - Peak Power : 1 kwatts - dB Value : 10 dB - SWR : 1.40 ~ 1.55

- Power Attenuator 20 dB : 4EA
 - DC to 18 GHz
 - Type N (F) to Type N (F)
 - Average Power : 100 watts
 - Peak Power : 1 kwatts
 - dB Value : 10 dB
 - SWR : 1.40 ~ 1.45

- Power Attenuator 30 dB : 4EA
 - DC to 18 GHz
 - Type N (F) to Type N (F)
 - Average Power : 100 watts
 - Peak Power : 1 kwatts
 - dB Value : 10 dB
 - SWR : 1.40 ~ 1.45