

# Specifications

품 명	Movable Noise Measurement Equipment
모 델 명	Movable Noise Measurement Equipment
세부 사양 (Specification)	<p><b>DAQ, MICROPHONE, SOFTWARE, BATTERY ETC Specification</b></p> <ol style="list-style-type: none"> <li>1) 4-ch Input Module LAN-XI 51.2kHz (Mic, CCLD,V)</li> <li>2) Battery Module for LAN-XI, including ZG-0469 mains charger and ZH-0686 adaptor</li> <li>3) PULSE LabShop 4 Channel FFT, Time Data Recorder and Reflex Core L4L and Data Viewer Pack (3099-A-N1, 7708-N, 7770-N4, 8700-N, 8701-N, 8702-L-N), Node-locked License</li> <li>4) Annual Software Maintenance and Support Agreement for PULSE LabShop 4 Channel FFT, Time Data Recorder and Reflex Core L4L and Data Viewer Pack (3099-A-N1, 7708-N, 7770-N4, 8700-N, 8701-N, 8702-L-N), Node-locked License</li> <li>5) 1/2" Free-field Microphone, 6 Hz to 20 kHz, Prepolarized, Incl. High Temperature Preamplifier 1706 with TEDS</li> <li>6) Cable, coax single screen, BNC (M) to BNC (M), 5,0m (16.7ft), max.+85° (185° )</li> <li>7) Tripod Adaptor for 1/2" microphone &amp; preamplifier assemblies</li> <li>8) Windscreen for 1/2" microphones, 90mm diameter</li> </ol>